

Frequently Used Commands of JC261P

Send these command in Command -> User-Defined section or send via SMS to set the advanced function

*There should be **no spaces** between any commands

For any further questions, please contact us: Amazon@Jimiiot.com

The part with <> is the parameter. Please modify the parameter range provided in the description to the value you need before sending.

No.	Function	Command	Reply Example	Explanation
1	Check Current Firmware Version	VERSION#	VERSION: KMC28_0_0_STD_J M_C261_V1.4.1.1_2 40330.2216	After upgrading the firmware, check and confirm whether the firmware upgrade is successful.
2	Connect Camera with WiFi Hotspot	WIFIAP,OFF#	OK!	N=WiFi's name P=WiFi's password
		SSID,2,<N>,<P>#	OK!	For Example: WiFi Name: Lncoon WiFi Password: LncoonJC261P Send: WIFIAP,OFF# Then send: SSID,2,Lncoon,LncoonJC261P#
3	Voice Prompt Setting	VOICESW,<A>#	OK!	A=Please enter the Value below; It defines the language of the voice prompts given out by the device, where in: 0-English, 1-Chinese, 2-Thai, 3-Arabic, 5-Russian, 7-Spanish, 8-Turkish, 9-Indonesian, 10-Vietam, 11-French, 14-Burmese,15-Deutsch,16-Hindi,17-Japanese,18-Korean,19-Urdu, 20-Bengali, 99=Mute For Example: To set the voice prompt into Spanish, send: VOICESW,7#

No.	Function	Command	Reply Example	Explanation
4	Set Video Watermark Speed in MPH	MILE,1#	OK!	A=0/1, 0 means kmh, 1 means mph
5	Set Video Watermark Speed in KMH	MILE,0#	OK!	A=0/1, 0 means kmh, 1 means mph
6	Enable Mileage Calculation	MILEAGE,ON#	OK!	Default Off, please enable when setup
7	Enable ADAS	ADASSW,1#	OK!	Default Off, please enable when setup. After opening, please set and calibrate various parameters of the car through WiFi Kit to obtain accurate ADAS alarms.
8	Enable Event GPS Location Upload	EVENTGPS,ON#	OK!	Default Off, please enable when setup
9	Disable the LEDs (For Discreet)	LED,OFF#	OK!	Default ON